





INST/LINE  
**CHANNEL 1**



LEVEL



LOW



HIGH

INST/LINE  
**CHANNEL 2**



LEVEL



LOW



HIGH

MIC/LINE  
**CHANNEL 3**



LOW Z LEVEL



HIGH Z LEVEL



LOW



MID



HIGH

**MASTER**



MAIN  
MONITOR



HEADPHONE



DDT

ENABLE

DEFEAT

POWER



CH 4/MONITOR



MASTER



DESIGNED AND MADE  
IN U.S.A.

**KB4**

ON



POWER

GROUND POLARITY



120 VAC 60 Hz



150 WATTS

PEAVEY ELECTRONICS CORPORATION  
MERIDIAN, MS USA

DESIGNED AND MADE  
IN THE USA



EXTERNAL SPEAKER  
MINIMUM 8 OHMS  
JACK PARALLELED WITH 8 OHM  
INTERNAL SPEAKER



MINIMUM AMPLIFIER LOAD: 4 OHMS  
75W RMS 8 OHMS  
100W RMS 4 OHMS  
20V RMS

MAIN LINE  
OUT

BALANCED  
LEFT



BALANCED  
RIGHT



HEAD  
PHONES



CH 4/  
MONITOR  
LINE  
INPUT



RETURN MAIN SEND  
EFX L



CHANNEL 3  
INPUT

RIGHT



LEFT/MONO



LOW Z  
RETURN



MIC  
EFX



CHANNEL 2  
INPUT



LEFT/MONO

RIGHT




INPUT OUTPUT



1 - GROUND  
2 - POSITIVE  
3 - NEGATIVE

SLEEVE  
TIP  
SLEEVE-GND  
TIP-POS

EFX  
RETURN SEND



CHANNEL 1  
INPUT



LEFT/MONO

RIGHT



PEAVEY ELECTRONICS CORPORATION  
MERIDIAN, MS USA  
120 VAC 60 Hz  
150 WATTS  
DESIGNED AND MADE IN THE USA  
MFG. LOC. 311